

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Canceled)
2. (Currently Amended) ~~The method of claim 1,~~ A method of determining that a signal has arrived at a receiver via a repeater, comprising:
 - a) receiving a signal at a wireless receiver, wherein the received signal includes signals originating from a plurality of distinct transmission stations,
 - b) comparing a predetermined pattern to information derived from the received signal, wherein the information is based on the signals originating from the plurality of distinct transmission stations; and
 - c) determining, based upon the predetermined pattern substantially matching the information derived from the received signal, that at least a portion of the received signal traveled via a repeater, and
wherein the predetermined pattern reflects a composite signal comprising a primary transmission signal of a base station transmitter mixed with a different secondary signal.
3. (Original) The method of claim 2, wherein the different secondary signal is a signal obtained from a distinct base station transmitter.
4. (Currently Amended) ~~The method of claim 1,~~ A method of determining that a signal has arrived at a receiver via a repeater, comprising:
 - a) receiving a signal at a wireless receiver, wherein the received signal includes signals originating from a plurality of distinct transmission stations,
 - b) comparing a predetermined pattern to information derived from the received signal, wherein the information is based on the signals originating from the plurality of distinct transmission stations; and
 - c) determining, based upon the predetermined pattern substantially matching the information derived from the received signal, that at least a portion of the received signal traveled via a repeater, and

wherein the predetermined pattern reflects a relationship between time of arrival of signals obtained from distinct base station transmitters.

5. (Currently Amended) ~~The method of claim 1,~~ A method of determining that a signal has arrived at a receiver via a repeater, comprising:

- a) receiving a signal at a wireless receiver, wherein the received signal includes signals originating from a plurality of distinct transmission stations,
- b) comparing a predetermined pattern to information derived from the received signal, wherein the information is based on the signals originating from the plurality of distinct transmission stations; and
- c) determining, based upon the predetermined pattern substantially matching the information derived from the received signal, that at least a portion of the received signal traveled via a repeater, and

wherein the predetermined pattern reflects relative strength of signals obtained from distinct base station transmitters.

6. (Original) The method of claim 5, wherein the predetermined pattern further reflects relative time of arrival of signals from a multiplicity of different base station transmitters.

7. (Original) The method of claim 6, wherein the signals are pilot symbols transmitted synchronously from a plurality of different base stations of a cellular telephone system.

8. (Canceled)

9. (Currently Amended) ~~The apparatus of claim 8,~~ Apparatus for determining that a signal has arrived at a receiver via a repeater, comprising:

- a) a receiver configured to derive information from a received wireless signal, wherein the received wireless signal includes signals originating from a plurality of distinct transmission sources, and wherein the information is based on the signals originating from the plurality of distinct transmission stations; and

b) a processing system in communication with the receiver and configured to:

- i) compare the information derived from the received signal to a stored set of predetermined parameters, and
- ii) determine that at least a portion of the received signal arrived via a repeater if the set of predetermined parameters describes an appropriate part of the information derived from the received signal, and
wherein the derived information reflects a relative time of arrival of distinct pilot sequences within the received signal.

10. (Currently Amended) ~~The apparatus of claim 8,~~ Apparatus for determining that a signal has arrived at a receiver via a repeater, comprising:

- a) a receiver configured to derive information from a received wireless signal, wherein the received wireless signal includes signals originating from a plurality of distinct transmission sources, and wherein the information is based on the signals originating from the plurality of distinct transmission stations; and
- b) a processing system in communication with the receiver and configured to:
 - i) compare the information derived from the received signal to a stored set of predetermined parameters, and
 - ii) determine that at least a portion of the received signal arrived via a repeater if the set of predetermined parameters describes an appropriate part of the information derived from the received signal, and
wherein the derived information reflects relative signal strength of distinct pilot sequences within the received signal.

11. (Original) The apparatus of claim 10, wherein the distinct pilot sequences include pilot sequences transmitted by distinct base station transmitters, and the derived information reflects a relative time of arrival of the distinct pilot sequences.

12. (Currently Amended) ~~The apparatus of claim 8,~~ Apparatus for determining that a signal has arrived at a receiver via a repeater, comprising:

a) a receiver configured to derive information from a received wireless signal, wherein the received wireless signal includes signals originating from a plurality of distinct transmission sources, and wherein the information is based on the signals originating from the plurality of distinct transmission stations; and

b) a processing system in communication with the receiver and configured to:

i) compare the information derived from the received signal to a stored set of predetermined parameters, and

ii) determine that at least a portion of the received signal arrived via a repeater if the set of predetermined parameters describes an appropriate part of the information derived from the received signal, and
 wherein the stored set of predetermined parameters reflects a composite signal comprising a primary transmission signal of a base station transmitter mixed with a different secondary signal.

13. (Currently Amended) The apparatus of claim 128, wherein the information derived from the received signal includes time of arrival and relative signal strength for each of a multiplicity of signals from distinct signal sources.

14. (Currently Amended) ~~The apparatus of claim 13;~~ Apparatus for determining that a signal has arrived at a receiver via a repeater, comprising:

a) a receiver configured to derive information from a received wireless signal, wherein the received wireless signal includes signals originating from a plurality of distinct transmission sources, and wherein the information is based on the signals originating from the plurality of distinct transmission stations; and

b) a processing system in communication with the receiver and configured to:

i) compare the information derived from the received signal to a stored set of predetermined parameters, and

ii) determine that at least a portion of the received signal arrived via a repeater if the set of predetermined parameters describes an appropriate part of the information derived from the received signal,

wherein the information derived from the received signal includes time of arrival and relative signal strength for each of a multiplicity of signals from distinct signal sources, and

wherein the receiver is a GPS-enabled cellular telephone handset configured to process CDMA signals, the multiplicity of signals include pilot signals from different CDMA base station transmitters, and the relative signal strength is related to chip energy divided by total signal.

15. (Canceled)

16. (Previously Presented) A method of creating a database having predetermined patterns for a method of determining that a signal has arrived at a receiver via a repeater, the method comprising:

- a) receiving a signal at a wireless receiver, wherein the information derived from the received signal comprises a constellation of signal parameters for signal components of a composite signal;
- b) identifying a pattern within information derived from the received signal; and
- c) storing parameters that describe the identified pattern as a reference repeater signature within the database.

17. (Original) The method of claim 16, wherein the constellation of signal parameters includes an indication of signal strength and an indication of time of arrival for each of a plurality of components of the composite signal.

18. (Original) The method of claim 17, wherein step b) further comprises identifying within the composite signal a plurality of component signal pairs, each pair arriving at times separated by a possible repeater excess delay.

19. (Original) The method of claim 16, wherein step b) further comprises:

- i) deriving information about location of the wireless receiver from parameters of a first set of component signals, and
- ii) determining that parameters of a second set of component signals are inconsistent with the derived location of the wireless receiver.

20. (Currently Amended) The method of claim ~~16~~15, wherein the wireless receiver is within a coverage area of a repeater server, and step b) further comprises comparing the information derived from the received signal with previous information derived from a signal received by a receiver differently located within the coverage area of the repeater server.

21. (Currently Amended) The method of claim ~~16~~15, further comprising revising an existing signature within the database based upon information derived from signals received by receivers determined on the basis of matching to the existing signature to be within a coverage area of a repeater associated with the existing signature.

22. (Canceled)

23. (Previously Presented) Apparatus for creating a database having predetermined patterns for use in a method of determining that a signal has arrived at a receiver via a repeater, the apparatus comprising:

a) a receiver configured to derive information from a received wireless signal, wherein the information derived by the receiver comprises a constellation of signal parameters for signal components of a composite signal; and

b) a processing system configured to:

i) obtain the derived information from the receiver,

ii) analyze the derived information to identify a pattern of at least a portion of the derived information, and

iii) store a description of the identified pattern in a database as a repeater signature reference pattern for determining if subsequent received signals arrived via a repeater.

24. (Original) The apparatus of claim 23, wherein the receiver is further configured to derive information including an indication of signal strength and an indication of time of arrival for each of a plurality of components of the composite signal.

25. (Original) The apparatus of claim 23, wherein the processing system is further configured to:

- i) derive information about location of the wireless receiver from parameters of a first set of component signals, and
- ii) determine that parameters of a second set of component signals are inconsistent with the derived location of the wireless receiver.

26. (Currently Amended) The apparatus of claim ~~23~~~~22~~, wherein the receiver is known to be located within a coverage area of a server of a repeater, and wherein the processing system is further configured to compare the information derived from the signal received from the receiver with information previously derived from a different signal received by a receiver differently located within the coverage area of the repeater.

27. (Currently Amended) The apparatus of claim ~~23~~~~22~~, wherein the processing system is further configured to

- i) determine that a subject receiver is within a coverage area of a repeater by comparing information derived from a signal received by the subject receiver with an existing repeater signature of the database, and
- ii) thereafter use the derived information of the subject receiver to modify the existing repeater signature.

28-40. (Canceled)

41. (Currently Amended) Apparatus for determining that a signal has arrived at a receiver via a repeater, comprising:

means for receiving a wireless signal including signals originating from a plurality of distinct transmission stations,

means for comparing a predetermined pattern to information derived from the received wireless signal, wherein the information is based on the signals originating from the plurality of distinct transmission stations; and

means for determining, based upon the predetermined pattern substantially matching the information derived from the received wireless signal, that at least a portion of the received wireless signal traveled via a repeater, and

wherein the predetermined pattern reflects a composite signal comprising a primary transmission signal of a base station transmitter mixed with a different secondary signal.

42. (Currently Amended) Apparatus for creating a database having predetermined patterns for use in the method of claim 16, comprising:

means for receiving a wireless signal including signals originating from a plurality of distinct transmission stations;

means for identifying a pattern within information derived from the received wireless signal, wherein the information derived from the received signal comprises a constellation of signal parameters for signal components of a composite signal~~is based on the signals originating from the plurality of distinct transmission stations~~; and

means for storing parameters that describe the identified pattern as a reference repeater signature within the database.